



## FEATURES

- DUAL CAGED FANS ROTATE 360° AROUND THE LIGHT
- FAN HEADS ARE MANUALLY ADJUSTABLE FROM 0-180°
- MOTORS REVERSIBLE VIA SWITCH ON MOTOR HOUSING
- MAINTENANCE-FREE SEALED BEARINGS
- CEILING MOUNT FOR FLAT OR VAULTED CEILINGS
- INCLUDED REMOTE CONTROL CONTROLS SPEED AND LIGHT ON/OFF AND DIMMING (WHEN USING DIMMABLE BULBS)
- LIGHT ASSEMBLY HAS 2 CANDELABRA SOCKETS LIMIT 60-WATT INCANDESCENT
- ACCEPTS LED BULBS - CANDELABRA BASE
- DAMP RATED FOR INDOOR OR OUTDOOR USE
- INCLUDES 10" EXTENSION ROD - AVAILABLE SEPARATELY 12", 24", 36", 48", 60" AND 72"
- EXTENSION ROD COUPLERS ARE AVAILABLE WHEN LONGER THAN 72" IS NEEDED
- COMMERCIAL OR RESIDENTIAL USE
- 10-YEAR INDOOR WARRANTY
- 5- YEAR OUTDOOR WARRANTY

## ENERGY INFORMATION AT HIGH SPEED

AIRFLOW	ELECTRICITY USE	AIRFLOW EFFICIENCY
3909	65	60
CUBIC FEET PER MINUTE	WATTS (EXCLUDES LIGHTS)	CUBIC FEET PER MINUTE PER WATT

\*DISCLAIMER: CEILING FAN MOTOR HAS BEEN TESTED WITH THE CORRESPONDENT SIZE BLADES.